

# BRICK WORKS



COLOURI



**NATURAL / BLACK**

**Wall** NATURAL Matte, NATURAL LINEAR Glossy  
7,5x20 - 2<sup>15</sup>/<sub>16</sub>"x7<sup>7</sup>/<sub>8</sub>"

**Furniture** BLACK  
7,5x20 - 2<sup>15</sup>/<sub>16</sub>"x7<sup>7</sup>/<sub>8</sub>"

**Floor** TR3ND CONCRETE WHITE  
60x60 - 23<sup>5</sup>/<sub>8</sub>"x23<sup>5</sup>/<sub>8</sub>"



**BLACK / GREY / ROSSO**

**Wall** ROSSO Glossy, BLACK Matte, GREY Matte/Glossy  
7,5x20 - 2'15/16"x7'7/8"

**Furniture** ROSSO LINEAR Glossy  
7,5x20 - 2'15/16"x7'7/8"

**Floor** STONETALK MINIMAL DARK  
90x90 - 35'7/16"x35'7/16"

COLOURS AND SIZES

**Brick Matte**

7,5x20 - 2<sup>15</sup>/<sub>16</sub>"x7<sup>7</sup>/<sub>8</sub>"




Grey



Natural



White




Rosso

**Brick Glossy**

7,5x20 - 2<sup>15</sup>/<sub>16</sub>"x7<sup>7</sup>/<sub>8</sub>"



Black



Grey




Natural



White



Teal



Rosso

**Brick Linear Glossy**

7,5x20 - 2<sup>15</sup>/<sub>16</sub>"x7<sup>7</sup>/<sub>8</sub>"



Black



Grey



Natural



White



Teal










Rosso


TRIMS

	Dimensione Size			
 Becco Civetta - Bullnose	<b>Matte</b> 7,5x20 - 2 <sup>15</sup> / <sub>16</sub> "x7 <sup>7</sup> / <sub>8</sub> " Pcs. Box 60		•	•
	<b>Glossy</b> 7,5x20 - 2 <sup>15</sup> / <sub>16</sub> "x7 <sup>7</sup> / <sub>8</sub> " Pcs. Box 60	•	•	•
	Dimensione Size			
 Becco Civetta - Bullnose	<b>Matte</b> 7,5x20 - 2 <sup>15</sup> / <sub>16</sub> "x7 <sup>7</sup> / <sub>8</sub> " Pcs. Box 60	•		•
	<b>Glossy</b> 7,5x20 - 2 <sup>15</sup> / <sub>16</sub> "x7 <sup>7</sup> / <sub>8</sub> " Pcs. Box 60	•	•	•


Porcelain Tiles  
ISO 13006 Annex G - UNI EN 14411 Annex G - Bla UGL  
ANSI A137.1 - CLASS P1




TECHNICAL FEATURES	STANDARD	VALUE	
 <b>WATER ABSORPTION</b>	UNI EN ISO 10545/3	Compliant	
	ASTM C373	Compliant	
 <b>MODULUS OF RUPTURE</b>	SPESSORE	<b>9 mm</b>	
	UNI EN ISO 10545/4	≥ 35 N/mm <sup>2</sup>	
 <b>BREAKING STRENGTH</b>	UNI EN ISO 10545/4	≥ 1300 N	
	ASTM C648	400 Lbs	
 <b>FROST RESISTANCE</b>	UNI EN ISO 10545/12	Compliant	
	ASTM C1026	Unaffected	
 <b>CHEMICAL RESISTANCE TO HIGH AND LOW ACID AND BASIC CONCENTRATIONS</b>	UNI EN ISO 10545/13	A - LA - HA	
	ASTM C-650	Unaffected	
 <b>STAIN RESISTANCE</b>	UNI EN ISO 10545/14	5	
	ASTM C1378	Class A	
 <b>SLIP RESISTANCE</b>		<b>MATTE</b>	<b>GLOSSY</b>
	DIN EN 16165 Annex B	-	-
	DIN EN 16165 Annex A	-	-
	ANSI A326.3:2017 DCOF	WET ≥ 0,42	-
	B.C.R.A. D.M. N. 236 14/6/89	-	-
	AS 4586-2013 Anexo A	-	-
	BS 7976-2: 2002 BSEN13036-4:2011 Pendulum testers	-	-
UNE 41901:2017 EX DB SUA (actual)	-	-	




PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL/COM/FGG UL 2818







放射性水平A类




15% 9,5 / 11,5 mm  
valori medi - average values





SHADE VARIATION



V2 Moderate

PACKING AND WEIGHT

Size cm	Thickness mm	Pieces x Sqm	Pieces x Box	Sqm x Box	Weight x Box	Boxes x Pal.	Sqm x Pal.	Weight x Pal.
7,5x20 Brick Matte - Glossy	9,5	66,67	60	0,900	19,80	60	54,00	803
7,5x20 Brick Linear Glossy	11,5	66,67	52	0,780	18,36	60	46,80	1103

Colours and optical features of the materials illustrated in this catalogue are to be regarded as mere indications. Product sizes indicated are nominal and like weights and colours undergo the typical variations of the ceramic process. The manufacturer reserves the right to change the technical and optical features of the materials illustrated at any time and without notice. These features are not legally binding.

SURFACE STATEMENTS

www.surfacestatements.com

# BRICK WORKS



COLOURI