

PLANKS OAK

TESORI



FLOOR Playbrick Golden Naturele R10 5,3x30 - 27/165 X 113/16





FLOOR Playangram Natural Naturale R10 Rett. 100x100 - 39^{5/8} x 39^{5/8}
Natural Naturale R10 Rett. 20x120 - 7^{7/8} x 47^{1/4}
FURNITURE Playbrick Natural Naturale R10 5.3x30 - 2^{1/16} x 11^{13/16}





FLOOR Raw Naturele R10 Rett. 20x120 - 7/16"x47 1/4"
WALL Playbrick Raw Naturele R10 5,3x30 - 2 1/16"x1 1 3/16"
FURNITURE Playbrick Raw Naturele R10 5,3x30 - 2 1/16"x1 1 3/16"





PLANKS OAK

9 mm.



Naturale R10 Rett.
20x120 - 7^{7/8}"x47^{1/4}"
Raw
60 patterns









Naturale R10 Rett.
20x120 - 7^{7/8}"x47^{1/4}"
Golden
60 patterns



Naturale R10 Rett.
20x120 - 7^{7/8}"x47^{1/4}"
Natural
60 patterns

TRIMS

	Size			
		Raw	Golden	Natural
 Skirting	Naturale R10 Rett. 4,6x120 - 1 ^{13/16} "x47 ^{1/4} " Pcs. Box 6 - LM x Box 7,20	•	•	•
 Step	Naturale R10 Rett. 33x120x3,2x3,2 1 ^{2^{15/16}} "x47 ^{1/4} "x1 ^{1/4} "x1 ^{1/4} " Pcs. Box 2 - LM x Box 2,40	•	•	•
 Corner Tile Right Left	Naturale R10 Rett. 33x120x3,2x3,2 1 ^{2^{15/16}} "x47 ^{1/4} "x1 ^{1/4} "x1 ^{1/4} " Pcs. Box 1 - LM x Box 1,20	Right •	Right •	Right •
		Left •	Left •	Left •



PLANKS OAK

9 mm. **PLAYTANGRAM** Naturale R10 Rett.
100x100 - 39^{3/8}"x39^{3/8}"



Raw
6 patterns



Golden
6 patterns

9,5 mm. **PLAYBRICK** Naturale R10
5,3x30 - 2^{1/16}"x11^{13/16}"




Natural
6 patterns



Raw
108 patterns



Golden
115 patterns



Natural
113 patterns










PLANKS OAK

Porcelain Tiles

ISO 13006 Annex G - UNI EN 14411 Annex G - Bla GL

ANSI A137.1 - CLASS P1



TECHNICAL FEATURES	STANDARD	VALUE	
 WATER ABSORPTION	UNI EN ISO 10545/3	Compliant	
	ASTM C373	Compliant	
 MODULUS OF RUPTURE	SPESSORE	9 / 9,5 mm	
	UNI EN ISO 10545/4	≥ 45 N/mm ²	
 BREAKING STRENGTH	UNI EN ISO 10545/4	≥ 2000 N	
	ASTM C648	≥ 400 lbf	
 FROST RESISTANCE	UNI EN ISO 10545/12	Compliant	
	ASTM C1026	Unaffected	
 CHEMICAL RESISTANCE TO HIGH AND LOW ACID AND BASIC CONCENTRATIONS	UNI EN ISO 10545/13	A - LA - HA	
	ASTM C-650	Unaffected	
 STAIN RESISTANCE	UNI EN ISO 10545/14	5	
	ASTM C1378	Class A	
 SLIP RESISTANCE		NATURALE	BRICK NATURALE
	DIN EN 16165 Annex B	R10	R10
	DIN EN 16165 Annex A	B (A+B)	-
	ANSI A326.3:2017 DCOF	WET ≥ 0,50	WET ≥ 0,50
	B.C.R.A. D.M. N. 236 14/6/89	> 0,40	> 0,40
	AS 4586-2013 Anexo A	P2	-
	BS 7976-2: 2002 BSEN13036-4:2011 Pendulum testers	< 36 Moderate Slip potential	< 36 Moderate Slip potential
UNE 41901:2017 EX DB SUA (actual)	-	-	




PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UL 2818



放射性水平A类



15% 9 / 9,5 mm
valori medi - average values



PACKING AND WEIGHT

Size cm	Thickness mm	Pieces x Sqm	Pieces x Box	Sqm x Box	Weight x Box Kg	Boxes x Pal.	Sqm x Pal.	Weight x Pal. Kg
20x120 Naturale R10	9	4,17	5	1,200	25,20	48	57,60	1210
100x100 Playtogram Naturale R10	9	1,00	2	2,000	40,00	24	48,00	960
5,3x30 Playbrick Naturale R10	9,5	63,00	34	0,540	12,00	80	43,24	960

Colours and optical features of the materials illustrated in this catalogue are to be regarded as mere indications. Product sizes indicated are nominal and like weights and colours undergo the typical variations of the ceramic process. The manufacturer reserves the right to change the technical and optical features of the materials illustrated at any time and without notice. These features are not legally binding.

SURFACE STATEMENTS

www.surfacestatements.com

PLANKS OAK



TESORI